

FR65 - Aluflame Work Molten Metal FR Jacket

Collection: Aluflame™

Range: Flame Resistant Multi-Norm

Shell Fabric: Aluflame Work: 43% Cotton, 30% Viscose, 20% Acrylic, 6% Para Aramid, 1% Carbon Fibre, 360g

Outer Carton: 18

Product information

Developed for the demanding environment of aluminium, iron and steel works, the inherent lightweight fabric offers maximum protection. This style is built for industrial washing and drying, while also suitable for domestic care—delivering long-lasting performance, reliability and ease of wear.

Aluflame™

Aluflame

Flame Resistant Multi-Norm

This industry leading flame resistant range provides multi-standard protection for hazardous environments. These state of the art products are the result of years of experience combined with advanced technology and market research. Commitment to the health, safety and comfort of the wearer can be seen in the wide range of products suitable for all climates and end uses.

Standards

EN ISO 11612 (A1+A2, B1, C1, D3, E3, F1)

EN ISO 11611 Class 2 (A1+A2)

EN 1149 -5

EN 61482-2 EN 61482-1-1 (ELIM 8.1 CAL/CM², ATPV 9.5 CAL/CM²)

EN 61482-2 EN 61482-1-2 APC 1

ASTM F1959/F1959M-14e1 (ATPV=13 Cal/CM² (HAF=84.9%))



Features

- High protection against aluminium molten metal splash
- Class 2 welding protection
- Certified protection against molten metal splash
- Industrial laundry wash at 75°C and tunnel dry at 155°C
- Stud adjustable cuffs for a secure fit
- Radio loops for easy clipping of a radio
- 2 pockets for secure storage
- 40+ UPF rated fabric to block 98% of UV rays
- Suitable to be worn in an ATEX environment
- CE-CAT III
- CE certified



PRODUCT SPECIFICATION & TECHNICAL DATA

FR65 - Aluflame Work Molten Metal FR Jacket Commodity Code: 6203391100

Test House

SATRA Technology Europe Ltd (Notified Body No.: NB: 2777)
Bracetown Business Park
D15 YN2P, Ireland
Cert No: 2777/25491-01/E00-00

Wash Care



Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	DUN14
FR65NARS	Navy	60.0	40.0	26.0	0.9290	0.0624	5036108352050	15036108840677
FR65NARM	Navy	60.0	40.0	26.0	0.9600	0.0624	5036108352043	15036108840660
FR65NARL	Navy	60.0	40.0	26.0	1.0020	0.0624	5036108352036	15036108840653
FR65NARXL	Navy	60.0	40.0	26.0	1.0580	0.0624	5036108352067	15036108840684
FR65NARXXL	Navy	60.0	40.0	26.0	1.0900	0.0624	5036108352074	15036108840691
FR65NARXXXL	Navy	60.0	40.0	26.0	1.1300	0.0624	5036108352081	15036108840707