

PW43 - Comfort Ear Defenders

Collection: Ear Muffs

Range: Hearing Protection

Materials: ABS, PVC, Polyurethane, Foam, EVA

Outer Carton: 28

Product information

These headband ear defenders are constructed to be both durable and ultra lightweight. Featuring broad foam cushions, high impact ABS cups filled with sound absorbing foam and comfort headband PW43 offers high noise attenuation (SNR 31dB).

Ear Muffs

Portwest Hearing protection range includes PPE with different level sound attenuation, to be adapted to various working environments giving the correct protection from dangerous noise, without isolating the workers. New models and colours for earmuffs allow a personalised choice. An updated range of earplugs complete our competitive and performing offer.

Hearing Protection

Hearing problems occur when you are exposed to hazardous working conditions without wearing the correct protective equipment.

Standards

EN 352-1 (SNR 31dB)

ANSI S3.19 (NRR 24dB)



Features

- Light and robust
- SNR 31dB attenuation level
- Ultra light and compact ear muff
- Padded headband for comfort
- Contrast colouring for added style
- Adjustable length for a secure and comfortable fit
- 100% Metal Free
- Retail bag which aids presentation for retail sales
- Individually packed for vending machines
- CE certified
- CE-CAT III

PW43 - Comfort Ear Defenders

Commodity Code: 3926909790

Test House

ALIENOR CERTIFICATION (Notified Body No.: 2754)

ZA du Sanital

86100, France

Cert No: 2754/1246/159/07/24/0457

Michael & Associates, Inc. (Notified Body No.:)

2766 W. College Ave Suite 1

PA 16801, United States

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	DUN14
PW43BKR	Black	65.0	43.0	55.0	0.2310	0.1537	5036108161430	15036108690548

PERFORMANCES - SOUND ATTENUATION - EN352-1:2002

PW43								
A	Frequency (Hz)	125	250	500	1000	2000	4000	8000
B	Means Attenuation (dB)	19.1	22.4	30.1	38.9	33.4	39.6	37.6
C	Standard Deviation (dB)	2.2	2.5	2.0	2.3	2.2	2.1	2.6
D	Assumed Protection (dB)	16.9	19.9	28.1	36.6	31.2	37.5	35.0
SNR = 32dB H = 34 dB / M = 30 dB / L = 23 dB								

PERFORMANCES - SOUND ATTENUATION - ANSI S3 19-1974 *Tested by Michael & Associates, Inc.*

	PW43									
A	Frequency(Hz)	125	250	500	1000	2000	3150	4000	6300	8000
B	Mean Attenuation (dB)	17.8	21.8	29.1	38.4	36.3	40.6	40.6	37.1	39.0
C	Standard Deviation (dB)	2.8	2.3	1.8	2.7	2.7	3.1	3.2	3.8	2.8
NNR (NOISE REDUCTION RATING) = 32dB										

PW43BKR